

Safety Data Sheet

(in accordance with Regulation (EU) 2015/830)

TECMA PAINT TERMIC FAHRENHEIT 10.8

Version: 3.1

Revision date: 04/01/2017

(Replaces the revision 3.0 date 01/06/15)

Página 1 of 8



SECTION 1: IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: TECMA PAINT TERMIC FAHRENHEIT 10.8
Product Code: 4198

1.2 Relevant identified uses of the mixture and uses advised against.

Professional use. Reflective protective coating.

Uses advised against: Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: **INDUSTRIAS QUIMICAS SATECMA, S.A.**
Address: Avda. La fundición, 69 - P. I. Santa Ana
City: Rivas - Vaciamadrid - 28522
Province: Madrid
Telephone: 916664711
Fax: 916664311
E-mail: correo@satecma.es
Web: www.satecma.es

1.4 Emergency telephone number: Industrias Químicas SATECMA S.A. Teléfono + 34 91 666 47 11. (Only available during office hours; Monday-Friday; 09:00-18:00)

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the mixture.

The product is not classified as hazardous within the meaning of Regulation (EU) No 1272/2008.

2.2 Label elements.

EUH statements:

EUH208 Contains mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.
EUH210 Safety data sheet available on request.

2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not Applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	specific concentration limit
Index No: 603-096-00-8 CAS No: 112-34-5 EC No: 203-961-6 Registration No: 01-2119475104-44-XXXX	[1] 2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether	< 2,5%	Eye Irrit. 2, H319	-

(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

Safety Data Sheet

(in accordance with Regulation (EU) 2015/830)

TECMA PAINT TERMIC FAHRENHEIT 10.8

Version: 3.1

Revision date: 04/01/2017

(Replaces the revision 3.0 date 01/06/15)



Página 2 of 8

[1] Substance with a Community workplace exposure limit (see section 8.1).

SECTION 4: FIRST AID MEASURES.

4.1 Description of first aid measures.

Due to the composition and type of the substances present in the product, no particular warnings are necessary.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

Eye contact.

If wearing contact lenses, remove them. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. **NEVER** use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. **NEVER** induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

No known acute or delayed effects from exposure to the product.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

SECTION 5: FIREFIGHTING MEASURES.

5.1 Extinguishing media.

Recommended extinguishing methods.

Extinguisher powder or CO₂. In case of more serious fires, also alcohol-resistant foam and water spray. Do not use a direct stream of water to extinguish.

5.2 Special hazards arising from the mixture.

Special risks.

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and gloves.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Product not classified as hazardous for the environment, avoid spillage as much as possible.

6.3 Methods and material for containment and cleaning up.

Pick up the spill with non-combustible absorbent materials (soil, sand, vermiculite, diatomite, etc.). Pour the product and the absorbent in an appropriate container. The contaminated area should be immediately cleaned with an appropriate de-

Safety Data Sheet

(in accordance with Regulation (EU) 2015/830)

TECMA PAINT TERMIC FAHRENHEIT 10.8

Version: 3.1

Revision date: 04/01/2017

(Replaces the revision 3.0 date 01/06/15)

Página 3 of 8



contaminator. Pour the decontaminator on the remains in an opened container and let it act various days until no further reaction is produced.

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

The product does not require special handling measures, the following general measures are recommended:

For personal protection, see section 8. Never use pressure to empty the containers. They are not pressure-resistant containers.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

The product does not require special storage measures.

As general storage measures, sources of heat, radiation, electricity and contact with food should be avoided.

Keep away from oxidising agents and from highly acidic or alkaline materials.

Store the containers between 5 and 35° C, in a dry and well-ventilated place.

Store according to local legislation. Observe indications on the label.

The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

Professional use. Reflective protective coating.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m ³
2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether	112-34-5	European Union [1]	Eight hours	10	67,5
			Short term	15	101,2
		United Kingdom [2]	Eight hours	10	67,5
			Short term	15	101,2

[1] According both Binding Occupational Exposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

[2] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adopted by Health and Safety Executive.

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
2-(2-butoxyethoxy)ethanol, diethylene glycol N. CAS: 112-34-5 N. CE: 203-961-6	DNEL (Workers)	Inhalation, Long-term, Local effects	67,5 (mg/m ³)
	DNEL (Workers)	Inhalation, Long-term, Systemic effects	67,5 (mg/m ³)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration: 100 %

Safety Data Sheet

(in accordance with Regulation (EU) 2015/830)

TECMA PAINT TERMIC FAHRENHEIT 10.8

Version: 3.1

Revision date: 04/01/2017

(Replaces the revision 3.0 date 01/06/15)

Página 4 of 8



Uses:		Useo profesional.	
Breathing protection:			
If the recommended technical measures are observed, no individual protection equipment is necessary.			
Hand protection:			
PPE:	Work gloves.		
Characteristics:	«CE» marking, category I.		
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420		
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.		
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.		
Material:	PVC (polyvinyl chloride)	Breakthrough time (min.):	> 480
		Material thickness (mm):	0,35
Eye protection:			
PPE:	Protective goggles with built-in frame.		
Characteristics:	«CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.		
CEN standards:	EN 165, EN 166, EN 167, EN 168		
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.		
Observations:	Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.		
Skin protection:			
If the product is handled correctly, no individual protection equipment is necessary.			



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Appearance: Pale white thixotropic liquid.

Colour: White

Odour: N.A./N.A.

Odour threshold: N.A./N.A.

pH: 8,3 ± 0,5

Melting point:

Boiling Point: N.A./N.A.

Flash point: > 100 °C

Evaporation rate: N.A./N.A.

Inflammability (solid, gas): N.A./N.A.

Lower Explosive Limit: N.A./N.A.

Upper Explosive Limit: N.A./N.A.

Vapour pressure: N.A./N.A.

Vapour density: N.A./N.A.

Relative density: 0,89 ± 0,03.

Solubility: N.A./N.A.

Liposolubility: N.A./N.A.

Hydrosolubility: N.A./N.A.

Partition coefficient (n-octanol/water): N.A./N.A.

Auto-ignition temperature: N.A./N.A.

Decomposition temperature: N.A./N.A.

Viscosity: 112 ± 10 KU a 25°C.

Explosive properties: N.A./N.A.

Oxidizing properties: N.A./N.A.

N.A./N.A.= Not Available/Not Applicable due to the nature of the product

9.2 Other information.

Volatile Organic Compound (VOC)

Subcategory of product: Products for exterior walls of mineral substrate, in aqueous base

Phase I * (as of 01/01/2007): 75 g / l

Phase II * (as of 01/01/2010): 40 g / l

(*) g/l ready for use

VOC content (w/w): 1.5%

VOC content: 14.988 g/ l

Safety Data Sheet

(in accordance with Regulation (EU) 2015/830)

TECMA PAINT TERMIC FAHRENHEIT 10.8

Version: 3.1

Revision date: 04/01/2017

(Replaces the revision 3.0 date 01/06/15)



Página 5 of 8

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.

The product does not present possibility of hazardous reactions.

10.4 Conditions to avoid.

Avoid any improper handling.

10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

SECTION 11: TOXICOLOGICAL INFORMATION.

11.1 Information on toxicological effects.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Splatters in the eyes can cause irritation and reversible damage.

Toxicological information about the substances present in the composition.

Name	Acute toxicity			
	Type	Test	Kind	Value
2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether	Oral	LD50	Rat	5660 mg/kg bw [1]
		[1] Dow Chemical Company Reports. Vol. MSD-41		
	Dermal	LD50	Rabbit	2700 mg/kg bw [1]
CAS No: 112-34-5 EC No: 203-961-6		[1] Journal of the American College of Toxicology. Vol. 12, Pg.139, 1993		
	Inhalation			

a) acute toxicity;

Not conclusive data for classification.

b) skin corrosion/irritation;

Not conclusive data for classification.

c) serious eye damage/irritation;

Based on available data, the classification criteria are not met.

d) respiratory or skin sensitisation;

Not conclusive data for classification.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Not conclusive data for classification.

Safety Data Sheet

(in accordance with Regulation (EU) 2015/830)

TECMA PAINT TERMIC FAHRENHEIT 10.8

Version: 3.1

Revision date: 04/01/2017

(Replaces the revision 3.0 date 01/06/15)



Página 6 of 8

h) STOT-single exposure;
Not conclusive data for classification.

i) STOT-repeated exposure;
Not conclusive data for classification.

j) aspiration hazard;
Not conclusive data for classification.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

Name	Ecotoxicity			
	Type	Test	Kind	Value
2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether CAS No: 112-34-5 EC No: 203-961-6	Fish	LC50	Lepomis macrochirus	1300 mg/l (96 h) [1] [1] Dawson, G.W., A.L. Jennings, D. Drozdowski, and E. Rider 1977. The Acute Toxicity of 47 Industrial Chemicals to Fresh and Saltwater Fishes. J.Hazard.Mater. 1(4):303-318 (OECDG Data File)
	Aquatic invertebrates	CE50	Daphnia magna	>1000 mg/l (48 h) [1] [1] DATOS DEL PROVEEDOR
	Aquatic plants	CE50	Scenedesmus subspicatus	>1000 mg/l (96) [1] [1] DATOS DEL PROVEEDOR

12.2 Persistence and degradability.

No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potencial.

Information about the bioaccumulation of the substances present.

Name	Bioaccumulation			
	Log Pow	BCF	NOECs	Level
2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether N. CAS: 112-34-5 EC No: 203-961-6	0,56	-	-	Very low

12.4 Mobility in soil.

No information is available about the mobility in soil.
The product must not be allowed to go into sewers or waterways.
Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

SECTION 13 DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Safety Data Sheet

(in accordance with Regulation (EU) 2015/830)

TECMA PAINT TERMIC FAHRENHEIT 10.8

Version: 3.1

Revision date: 04/01/2017

(Replaces the revision 3.0 date 01/06/15)



Página 7 of 8

Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transportation is not dangerous. In case of road accident causing the product's spillage, proceed in accordance with point 6.

14.1 UN number.

Transportation is not dangerous.

14.2 UN proper shipping name.

Description:

ADR: Transportation is not dangerous.

IMDG: Transportation is not dangerous.

ICAO: Transportation is not dangerous.

14.3 Transport hazard class(es).

Transportation is not dangerous.

14.4 Packing group.

Transportation is not dangerous.

14.5 Environmental hazards.

Transportation is not dangerous.

14.6 Special precautions for user.

Transportation is not dangerous.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.

Transportation is not dangerous.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

The product is not affected by Directive 2012/18/EU (SEVESO III).

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

15.2 Chemical safety assessment.

There has been no evaluation a chemical safety assessment of the product.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H319 Causes serious eye irritation.

Classification codes:

Eye Irrit. 2 : Eye irritation, Category 2

Sections modified from the previous version: 2.2 and 16. This version of the SDS supersedes all previous.

It is recommended that the product only be employed for the purposes advised.

Safety Data Sheet

(in accordance with Regulation (EU) 2015/830)

TECMA PAINT TERMIC FAHRENHEIT 10.8



Version: 3.1

Revision date: 04/01/2017

(Replaces the revision 3.0 date 01/06/15)

Página 8 of 8

Abbreviations and acronyms used:

BCF: Bioconcentration factor.

CEN: European Committee for Standardization.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

EC50: Half maximal effective concentration.

PPE: Personal protection equipment.

LC50: Lethal concentration, 50%.

LD50: Lethal dose, 50%.

Log Pow: Logarithm of the partition octanol-water.

NOEC: No observed effect concentration.

Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>

<http://echa.europa.eu/>

Regulation (EU) 2015/830.

Regulation (EC) No 1907/2006.

Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.